



Product Data Sheet

VISCOTAQ[®] SEALANT/EZ PASTE

- 1. Product Description.** VISCOTAQ SEALANT is a versatile and economical product intended for a wide range of structural applications, where water leaks are a problem. VISCOTAQ SEALANT provides for a quick and economical method of installation with excellent sealing properties. VISCOTAQ SEALANT has immediate adhesion to steel, PE, PP, epoxy, polyurethane, PVC, etc. without roughening. There is no cure or hardening time required. VISCOTAQ[®] SEALANT is storage stable (dry/cool) with an unlimited shelf life.
- 2. Applications.** VISCOTAQ[®] SEALANT is engineered for use in many water leak applications, offering long-term performance in commercial, residential, telecommunications, utilities, transportation, electrical, water, wastewater, agricultural, and industrial as well as others. The primary applications are sealing around rooftop vents, pipes, metal roof seams, flashings, residential and commercial roofing, EPM roofing, and cable entries, holes and voids, cracks, storage tanks, industrial pools, swimming pools, manholes, basements, floors, cable joints and repairs, and etc. VISCOTAQ SEALANT is also used in conjunction with other AMCORR Products such as EZ Wrap for application at the tank chime (floor wall interface) and at flanges to prevent corrosion.
- 3. Physical Properties.**

Product Name:	VISCOTAQ [®] SEALANT
Color:	white
Odor:	None
Density:	1.4
Viscosity:	Mastic-like
Ph:	Neutral
Shelf Life:	Unlimited
Max. Operating Temp.	158 F
Min. Operating Temp.	-45 F
Water Intake:	0%
Adheres to Wet Surface:	Yes, most cases
Min. Temp. (no cracks)	-45 F
Application:	Above and below grade applications
Stretch:	>500% (putty)
Chemical behavior:	completely inert. Can be used in conjunction with gaskets and seals



4. Performance. VISCOTAQ SEALANT® is a permanent solution to a variety of water problems. VISCOTAQ® SEALANT has been highly successful in solving water leakage problems in numerous markets. Consult AMCORR Products for information regarding these projects and references.

5. Specifications. The VISCOTAQ SEALANT® is a mastic-like material designed with synthetic properties that will adhere to almost any surface without a primer. The VISCOTAQ SEALANT® is available in cartridges and is designed to be used as a permanent solution for numerous water leaks.

6. Installation Instructions.

- Clean the application with a dry cloth. Remove as much of the loose material on the area as you can.
- Apply the sealant by cartridge and press the product in the area. Ensure the area is clean
- In many cases the application can be done in wet environment.
- When more head pressure is expected, cover with cementitious grout or a rubber seal, since the product remains flexible.
- For cable conduits, apply a minimum of 2 inch in depth.

7. Maintenance. INSPECTION: visually inspect to see if full adhesion has occurred (within half an hour to an hour). If not full adhesion has occurred, reapply with caulking gun by injecting more product. In case of active leak: leak should have stopped.

8. Technical Service. AMCORR provides technical support to assist in product selection and appropriate installation design. Technical information is available upon request.

9. Precautionary Information. No unusual hazards are known or expected. Observe normal safety procedures during installation. MSDS Sheets are available upon request.

10. Availability. VISCOTAQ SEALANT® is available from authorized distributors nationwide.

Important Notice: All statements, technical information, and recommendations contained herein are based upon testing believed to be reliable, but the accuracy and completeness thereof is not guaranteed.

Warranty: AMCORR PRODUCTS manufactures its goods in a manner to be free of defects. Should any defect occur in its goods (within one year), AMCORR PRODUCTS, upon prompt notification, will at its option, exchange or repair the goods.