



VISCOTAQ® Tank Chime Sealant

The VISCOTAQ® Chime Sealant System is based upon the use of Viscotaq EZ Wrap in combination with the ViscoSealant. VISCOTAQ® is a viscous elastic synthetic material that remains flexible and tacky during its entire life. Since the floor plate of a tank is constantly moving during the filling and emptying process, flexibility and aggressive adhesion is of utmost importance. The VISCOTAQ® Chime Sealant System is used to prevent water infiltration at the concrete ring wall interface of the tank, a place where corrosion normally occurs. The VISCOTAQ® Chime Sealant System can be installed on new and existing facilities. The system can be painted immediately after installation and does not interfere with any future paint, inspection and maintenance programs according to API 653.

APPLICATION:

- Clean steel chime surface and concrete ring by power wash. Let dry.
- Apply the VISCOSEALANT minimum 1 inch deep into annular space between steel and concrete ring. Use a putty knife to smoothen down.
- Apply VISCOTAQ® EZ Wrap from the floor wall weld (butt up against the weld) to the concrete ring. Allow for 2 inch overlap on concrete ring.
- Use a seam roller to press down the VISCOTAQ® EZ Wrap.
- Product can be painted immediately.

THE PROPERTIES:

- Easy to apply
- Permanent flexibility
- Permanent adhesion
- SP 2 cleaning
- Long term protection
- Non toxic
- Weather/salt resistant freeze/thaw resistant
- -30 to 158 F
- Technology filed for patents
- cold applied
- environmental friendly
- no primers
- UV RESISTANT
- CP RESISTANT
- Molds and forms easily
- Solving difficult problems
- Compatible with nowadays available coatings
- Tested according to latest specifications
- ISO9001
- Made in the USA
- 70 mils
- Tested to latest ASTM and CSA standards

